

## Technical Data Sheet

### OL3000/00 OIL FOR WOOD TREATMENT

Supersedes previous issue dated 10.09.18

DATE 05 december 2019

Area of use:	Various type of wood and parquet
Method of use:	Spray, brush and wiping, roller
Thinning:	ready to use (dilutable 10 - 30%)

#### Technical characteristics

Solids content (%):	52 ± 1
Specific gravity (kg/l):	0.93 ± 0.030
Viscosity (DIN 6 at 20°C):	32" ± 3"

#### General characteristics

Recommended application weight (gr/m <sup>2</sup> ):	from 30 to 80
Drying time (50 g/m <sup>2</sup> at 20°C):	Touch-dry 4 – 6 h
	Stackable 24 – 36 h
Number of coats:	2-more
Shelf-life (months):	12 month
	After long periods of storage, always check homogeneity and stir well before use to eliminate any possible sediment.

OL3000/00 is an urethane oil especially developed for parquet application, both interior and exterior.

We suggest to sand the raw wood with 180 sandpaper, then proceed to apply at least 2 coats of oil to obtain better chemical and mechanical resistance. Sand with 320 sandpaper between layers.

To achieve the best wood wetting we suggest to dilute the first coat with 10%-30% (depending on the application) of a thinner as DE0703/00, especially if applied by spraygun.

After the application of the oil we suggest to remove the excess of product by using a wipe. It's possible anyway not to brush the last layer of oil to achieve better resistance.

It's possible to treat parquet for exterior too, in this case it's suggested to tint the first layer of oil with XEL3609/XX and/or XE4150/XX or alternatively a EM0556/XX to achieve the best performance. An annual maintenance will be necessary (cleaning before the panel).

In exterior application is very important to close carefully the end grain to prevent water swelling.

Remember to wash the used wipe with water before trashing them. They are subject to self-ignition.